



GATOR TRAP

Microbial Grease Trap and Drain Cleaner

GATOR INTERNATIONAL
www.gatorinternational.com

Grease Traps and Drains

1. Have the grease trap pumped.
2. Mix the microbes with the biocatalyst solution.
3. Apply 1-2 gallons of **GATOR TRAP** directly into grease trap first application, spray sides of trap to begin cleaning process of walls and to develop a colony of microbes.
4. Allow the trap to fill with water.
5. For typical restaurants, add 1-2 gallons of **GATOR TRAP** (depending on size of trap, number of meals served, and frequency of pumping) per month directly into grease trap, preferably using a parastolic (chemical release) pump. Consult your distributor for installation and maintenance instructions.
6. Use **GATOR TRAP** in a systematic maintenance program for washing floors, counters, hoods, vents, filters, etc. Use **GATOR TRAP** one-to-one on initial application. Then mix approximately 1 pint of **GATOR TRAP** with 1 gallon of warm soap or wash water. Use at least every other day.
7. For drains, pour 1 gallon of **GATOR TRAP** down the drains furthest from the septic tank/grease trap every 90 days. Allow to stand in the lines overnight.

NOTE: Remember the microbes will die if they come in contact with pure bleach or any chemical causing a pH over 11 or less than 4 to occur. Do not expose to water temperatures in excess of 120 degrees. (Typical grease trap temperature is 100 degrees.